

LINER PROTECTION FELT FOR SWIMMING POOLS

GEOTEXTILE GREY COLOR MADE WITH FUSIONBONDING FIBRES OF POLYPROPYLENE AND FUNGICIDE TREATMENT THAT AVOIDS PROLIFERATION OF ALGAE AND FUNGI FROM INSIDE THE POOL.

EFFICIENT PROTECTION BARRIER (WALLS AND BOTTOM) BETWEEN FOUNDATIONS (CONCRETE OR WOOD) AND PVC MEMBRANE.

PROTECTS AGAINST PERFORATION.

HIDES ANY IMPERFECTIONS OF CONCRETE WALLS.

MANDATORY USE IN BUTT WELDING METHOD.

SURFACE	NEEDLEPUNCHED FELT
FIBRES	100% PP inert material + Fungicide treatment
WEIGHT	350 g/m ² ± 10%
THICKNESS	2.70 mm ± 10%
TRACTION RESISTANCE	L: 9 000 N/m T: 16 500 N/m
ELONGATION	L: 86% T: 83%
ROLL WIDTH	200 cm
ROLL LENGHT	30 m
ROLL DIAMETER	35 cm

INSTALLATION:

- CLEAN THE CONCRETE TO REMOVE ALL THE DUST
- SMOOTH SURFACE TOWARDS LINER
- SLIGHTLY FIBROUS SURFACE: CONCRETE OR WOOD SIDE
- FIX IT WITH DOUBLE SIDED TAPE OR A WATERPROOF SPRAY GLUE